



P

产品介绍
products Introduction

TRUCK TYRE CHANGER T568



Wireless Remote Control Unit
of T568, 遥控可选



- SEMI-AUTOMATIC TRUCK TYRE CHANGER T568 UNIVERSAL SELF-CENTERING CHUCK RIM CAPACITY 14" - 26"
- CLOCKWISE AND ANTICLOCKWISE ROTATION OF CHUCK
- ITALIAN PUMP OPTIONAL
- 可移动式/低压控制手柄进行操作
- 操作电压24V/安全稳定
- 可摆动装配圆盘和可摆动装配勾的通用装配臂
- 适用于14" -26" 全部轮胎尺寸
- 举升臂和夹具均为液压驱动
- 意大利泵可选

OPTIONAL ACCESSORIES 可选配件



Alu alloy rims protection rings
铝合金轮胎保护圈



Tubeless roller 真空胎压滚



Alu alloy rims protection set
铝合金轮胎保护套

TECHNICAL DATA 技术参数

Rim diameter 轮胎直径	14" -28"
Max.wheel weight 最大车轮重量	500kg
Max.wheel width 最大车轮宽度	780mm
Max.tyre diameter 最大轮胎直径	1600mm
Hydraulic pump motor 液压动力单元	1.5kw 380v~3ph(220v Optional)
Gearbox motor 齿轮箱电机	1.8kw 380v~3ph(220v Optional)
Band breaker force 胎边压力	2500N
Operation control voltage 移动控制手柄电压	24V
Machine weight approx. 设备重量	570kg
Overall dimensions approx. 设备占地面积	2500 * 2000mm
Power 电压	220/400V 50/60Hz/TP3P Optional

WEIGHT&DIMENSIONS 重量&包装尺寸

Model	Gross Weight (kg)	Outside Dimension L*W*H (mm)
T568	647	2030*1600*1000

STANDARD ACCESSORIES 标准配件



PACKAGING 包装尺寸

